

Rectangular Duct

Kolsten Rectangular Duct & Fittings meet ASTM-A653-96 standards

304 Stainless Steel = ASTM-A-240

316L Stainless Steel = ASTM-A-240

Aluminum 3003H14 = ASTM-B-209

Galvanized Metal = ASTM-A-653-96

Reference SMACNA tables 1" - 10" W.G. for construction standards and reinforcement schedule

Kolsten Rectangular Duct & Fittings are fabricated from galva-nized steel & is in accordance with the latest edition of SMACNA Duct construction standards.

*Note: Check to indicate variations from standard construction methods

Coil Line Finish Lengths		
Connectors	60"	48"
TDC/TDC	56 1/4	44 1/4
TDC/S&D	57 5/8	45 5/8
TDC/DM 35	58 1/8	46 1/8
TDC/RAW	58 1/8	46 1/8
TDC/CAPS	57 1/2	45 1/2
TDC/CAPL	57 1/4	45 1/4
TDC/NOTCH	57 1/8	45 1/8
S&D/S&D	59	47
S&D/DM 35	59 1/2	47 1/2
S&D/RAW	59 1/2	47 1/2
S&D/CAPS	58 7/8	46 7/8
S&D/CAPL	58 5/8	46 5/8
S&D NOTCH	58 1/2	46 1/2
RAW/RAW	60	48
CAPS/RAW	59 3/8	47 3/8
CAPL/RAW	59 1/8	47 1/8
CAPS/CAPS	58 3/4	46 3/4
CAPL/CAPL	58 1/4	46 1/4
DM 35/DM 35	60	48

Alternative Joint Connectors*

S & D / SS & D

TDC

Ductmate

Seam Construction *

Pittsburg

Snap-Lock

Reinforcement Options*

External Angle Iron

Internal Tie Rods

Seam Sealant Available*

Yes

No

Job Name: _____

Location: _____

Mechanical Contractor: _____

Job No: _____

Manufacturer: Kolsten Industrial (480) 339-1990

Date: _____