

Rectangular Duct / Aluminum 3003 H14

Kolsten Aluminum Rectangular Duct & Fittings meets ASTM-B209 standards

Kolsten Rectangular Duct & Fittings are fabricated from Aluminum 3003 H14 & is in accordance with the latest edition of SMACNA Duct construction standards.

Reference SMACNA tables 1" - 10" W.G. for construction standards and reinforcement schedule

Seam Construction unless otherwise specified will be Pittsburg, Quick-lok and Rivet.

Coil Line Finish Lengths		
Connectors	60"	48"
TDC/TDC	56 1/4	44 1/4
TDC/S&D	57 5/8	45 5/8
TDC/DM 35	58 1/8	46 1/8
TDC/RAW	58 1/8	46 1/8
TDC/CAPS	57 1/2	45 1/2
TDC/CAPL	57 1/4	45 1/4
TDC/NOTCH	57 1/8	45 1/8
S&D/S&D	59	47
S&D/DM 35	59 1/2	47 1/2
S&D/RAW	59 1/2	47 1/2
S&D/CAPS	58 7/8	46 7/8
S&D/CAPL	58 5/8	46 5/8
S&D NOTCH	58 1/2	46 1/2
RAW/RAW	60	48
CAPS/RAW	59 3/8	47 3/8
CAPL/RAW	59 1/8	47 1/8
CAPS/CAPS	58 3/4	46 3/4
CAPL/CAPL	58 1/4	46 1/4
DM 35/DM 35	60	48

*Note: Check to indicate variations from standard construction methods

Alternative Joint Connectors*

- TDC / TDF
- Ductmate
- S & D / SS & D

Seam Construction*

- Pittsburg
- Other

Reinforcement Options*

- External Angle Iron
- Internal Tie Rods

Seam Sealant Available*

- Yes
- No

Job Name: _____

Location: _____

Mechanical Contractor: _____

Job No: _____

Manufacturer: Kolsten Industrial (480) 339-1990

Date: _____